



| 物料编号               | 型号      | 额定电压 | 规格     | 导体结构     | 近似外径<br>mm | 近似重量<br>KG/KM | 导体电阻<br>Ω/km |
|--------------------|---------|------|--------|----------|------------|---------------|--------------|
| ANM03.018.01.019AB | UL10699 | 600V | 19AWG  | 43/0.14  | 2          | 8.48          | 27.4Ω/km     |
| ANM03.018.01.018AB | UL10699 | 600V | 18AWG  | 29/0.19  | 2.1        | 10.23         | 21.8Ω/km     |
| ANM03.018.01.017AB | UL10699 | 600V | 17AWG  | 37/0.19  | 2.35       | 12.51         | 17.3Ω/km     |
| ANM03.018.01.016AB | UL10699 | 600V | 16AWG  | 27/0.25  | 2.45       | 15.21         | 13.7Ω/km     |
| ANM03.018.01.015AB | UL10699 | 600V | 15AWG  | 34/0.25  | 2.65       | 18.72         | 10.9Ω/km     |
| ANM03.018.01.014AB | UL10699 | 600V | 14AWG  | 43/0.25  | 2.85       | 23.08         | 8.62Ω/km     |
| ANM03.018.01.013AB | UL10699 | 600V | 13AWG  | 54/0.25  | 3.15       | 28.72         | 6.82Ω/km     |
| ANM03.018.01.012AB | UL10699 | 600V | 12AWG  | 68/0.25  | 3.35       | 35.44         | 5.43Ω/km     |
| ANM03.018.01.011AB | UL10699 | 600V | 11AWG  | 85/0.25  | 4.15       | 47.00         | 4.30Ω/km     |
| ANM03.018.01.010AB | UL10699 | 600V | 10AWG  | 108/0.25 | 4.8        | 58.73         | 3.409Ω/km    |
| ANM03.018.01.009AB | UL10699 | 600V | 9AWG   | 136/0.25 | 5.5        | 76.16         | 2.705Ω/km    |
| ANM03.018.01.008AB | UL10699 | 600V | 8AWG   | 171/0.25 | 5.9        | 93.68         | 2.144Ω/km    |
| ANM03.018.01.007AB | UL10699 | 600V | 7AWG   | 84/0.4   | 6.3        | 115.45        | 1.700Ω/km    |
| ANM03.018.01.006AB | UL10699 | 600V | 6AWG   | 106/0.4  | 7.1        | 143.50        | 1.348Ω/km    |
| ANM03.018.01.005AB | UL10699 | 600V | 5AWG   | 134/0.4  | 7.7        | 178.04        | 1.070Ω/km    |
| ANM03.018.01.004AB | UL10699 | 600V | 4AWG   | 169/0.4  | 9          | 230.93        | 0.8481Ω/km   |
| ANM03.018.01.003AB | UL10699 | 600V | 3AWG   | 213/0.4  | 9.8        | 286.30        | 0.6727Ω/km   |
| ANM03.018.01.002AB | UL10699 | 600V | 2AWG   | 268/0.4  | 10.8       | 355.59        | 0.5335Ω/km   |
| ANM03.018.01.001AB | UL10699 | 600V | 1AWG   | 338/0.4  | 12.1       | 450.87        | 0.4230Ω/km   |
| ANM03.018.01.1/0AB | UL10699 | 600V | 1/0AWG | 426/0.4  | 13.4       | 561.74        | 0.3354Ω/km   |
| ANM03.018.01.2/0AB | UL10699 | 600V | 2/0AWG | 537/0.4  | 14.7       | 699.60        | 0.2660Ω/km   |
| ANM03.018.01.3/0AB | UL10699 | 600V | 3/0AWG | 677/0.4  | 16.1       | 871.79        | 0.2110Ω/km   |
| ANM03.018.01.4/0AB | UL10699 | 600V | 4/0AWG | 854/0.4  | 17.7       | 1088.94       | 0.1673Ω/km   |