

物料编号	型号	规格	额定电压	导体结构	电缆近似外径 mm	近似重量 kg/km	导体电阻Ω/km
ANO06.002.03.000.50B	H05VVC4V5-K	3 G0.5	300/500V	18/0.19	10	111.3	39.00
ANO06.002.04.000.50B	H05VVC4V5-K	4 G0.5	300/500V	18/0.19	10.7	132.7	39.00
ANO06.002.05.000.50B	H05VVC4V5-K	5 G0.5	300/500V	18/0.19	11.6	162.7	39.00
ANO06.002.07.000.50B	H05VVC4V5-K	7 G0.5	300/500V	18/0.19	13.5	207.7	39.00
ANO06.002.12.000.50B	H05VVC4V5-K	12 G0.5	300/500V	18/0.19	16.2	295	39.00
ANO06.002.03.000.75B	H05VVC4V5-K	3 G0.75	300/500V	27/0.19	10.4	129.4	26.00
ANO06.002.04.000.75B	H05VVC4V5-K	4 G0.75	300/500V	27/0.19	11.3	163.6	26.00
ANO06.002.05.000.75B	H05VVC4V5-K	5 G0.75	300/500V	27/0.19	12.1	188.6	26.00
ANO06.002.07.000.75B	H05VVC4V5-K	7 G0.75	300/500V	27/0.19	14.3	246.9	26.00
ANO06.002.12.000.75B	H05VVC4V5-K	12 G0.75	300/500V	27/0.19	17.1	354.3	26.00
ANO06.002.18.000.75B	H05VVC4V5-K	18 G0.75	300/500V	27/0.19	19.8	517	26.00
ANO06.002.25.000.75B	H05VVC4V5-K	25 G0.75	300/500V	27/0.19	23	677.8	26.00
ANO06.002.34.000.75B	H05VVC4V5-K	34 G0.75	300/500V	27/0.19	26.2	860.6	26.00
ANO06.002.03.001.00B	H05VVC4V5-K	3 G 1.0	300/500V	35/0.19	11	144.8	19.50
ANO06.002.04.001.00B	H05VVC4V5-K	4 G 1.0	300/500V	35/0.19	11.7	180.8	19.50
ANO06.002.05.001.00B	H05VVC4V5-K	5 G 1.0	300/500V	35/0.19	12.8	209	19.50
ANO06.002.07.001.00B	H05VVC4V5-K	7 G 1.0	300/500V	35/0.19	15.1	273	19.50
ANO06.002.12.001.00B	H05VVC4V5-K	12 G 1.0	300/500V	35/0.19	17.9	427.6	19.50
ANO06.002.18.001.00B	H05VVC4V5-K	18 G 1.0	300/500V	35/0.19	20.8	598.6	19.50
ANO06.002.25.001.00B	H05VVC4V5-K	25 G 1.0	300/500V	35/0.19	24.2	791.8	19.50
ANO06.002.34.001.00B	H05VVC4V5-K	34 G 1.0	300/500V	35/0.19	27.7	1,003.9	19.50
ANO06.002.03.001.50B	H05VVC4V5-K	3 G 1.5	300/500V	31/0.25	12.1	189.7	13.30
ANO06.002.04.001.50B	H05VVC4V5-K	4 G 1.5	300/500V	31/0.25	13.2	221.6	13.30
ANO06.002.05.001.50B	H05VVC4V5-K	5 G 1.5	300/500V	31/0.25	14.7	261.8	13.30
ANO06.002.07.001.50B	H05VVC4V5-K	7 G 1.5	300/500V	31/0.25	17.4	356.7	13.30
ANO06.002.12.001.50B	H05VVC4V5-K	12 G 1.5	300/500V	31/0.25	20.6	559.4	13.30
ANO06.002.18.001.50B	H05VVC4V5-K	18 G 1.5	300/500V	31/0.25	24	767.6	13.30
ANO06.002.25.001.50B	H05VVC4V5-K	25 G 1.5	300/500V	31/0.25	28	1049	13.30
ANO06.002.03.002.50B	H05VVC4V5-K	3 G2.5	300/500V	51/0.25	14	241.5	7.98
ANO06.002.04.002.50B	H05VVC4V5-K	4 G2.5	300/500V	51/0.25	15.5	298.3	7.98
ANO06.002.05.002.50B	H05VVC4V5-K	5 G2.5	300/500V	51/0.25	17.2	363.7	7.98
ANO06.002.07.002.50B	H05VVC4V5-K	7 G2.5	300/500V	51/0.25	20.3	487.2	7.98
ANO06.002.12.002.50B	H05VVC4V5-K	12 G2.5	300/500V	51/0.25	24.3	743.6	7.98