

电缆参数  
芯线名称： SIHF

AWG	芯数	导体横截面积 MM2	标称外径 MM	铜重量 KG/KM
20	2	0.5	5.5	9.6
20	3	0.5	5.8	14.5
20	4	0.5	6.2	19.3
20	5	0.5	6.8	24
20	6	0.5	7.4	28.9
20	7	0.5	7.4	33.7
20	8	0.5	8.6	38.4
20	10	0.5	9.5	48.1
20	12	0.5	9.8	57.6
20	16	0.5	11	76.7
20	18	0.5	11.5	86.5
20	25	0.5	13.7	120
18	2	0.75	6.4	14.4
18	3	0.75	6.8	21.6
18	4	0.75	7.8	29
18	5	0.75	8.5	36
18	6	0.75	9.2	43
18	7	0.75	9.2	50
18	8	0.75	9.7	57.7
18	10	0.75	10.9	72.1
18	12	0.75	11.1	86.5
18	16	0.75	12.6	115.2
18	18	0.75	13.3	129.7

18	25	0.75	15.6	180
17	2	1	6.6	19
17	3	1	7.4	29
17	4	1	8	38
17	5	1	8.8	48
17	6	1	9.5	58
17	7	1	9.5	67
17	8	1	10.4	76.7
17	10	1	11.3	96.1
17	12	1	11.5	115.2
17	16	1	13.1	153.5
17	18	1	13.8	172.9
17	25	1	16.2	240
16	2	1.5	7.6	29
16	3	1.5	8	43
16	4	1.5	8.8	58
16	5	1.5	9.6	72
16	6	1.5	10.4	86
16	7	1.5	10.4	101
16	8	1.5	11.6	114
16	10	1.5	13.6	116
16	12	1.5	14.6	173
16	14	1.5	15.4	202
16	16	1.5	16.7	231
16	18	1.5	17.6	260
16	20	1.5	18.2	288
16	24	1.5	20	346

14	2	2.5	9.2	48
14	3	2.5	9.7	72
14	4	2.5	10.6	96
14	5	2.5	11.6	120
14	6	2.5	12.9	144
14	7	2.5	13	168
14	8	2.5	14.9	192.2
14	10	2.5	16.5	240.1
14	12	2.5	17.8	288
14	16	2.5	19.1	384
14	18	2.5	20	432
14	25	2.5	24.5	600
12	2	4	10.8	77
12	3	4	11.4	115
12	4	4	13.1	154
12	5	4	14.4	192
12	7	4	16.2	269
10	2	6	13.4	115
10	3	6	14.2	173
10	4	6	16.2	230
10	5	6	17.7	288
10	7	6	19.2	403
8	2	10	17.6	192
8	3	10	18.7	288
8	4	10	20.4	384
8	5	10	22.5	480
8	7	10	24.4	672.2

6	2	16	20.4	308
6	3	16	22	462
6	4	16	24.3	616
6	5	16	26.7	770
6	7	16	27.6	1075.3
4	2	25	24.6	480
4	3	25	26.2	720
4	4	25	31.8	960
2	2	35	28.2	672
2	3	35	29.9	1008
2	4	35	32.8	1344